
















## WORKLITE® PANELS

EPS Foamkore®			PHC Hexkore™			XPS Foamkore®		
<b>Core Material</b>								
 Expanded Polystyrene			 Paperboard Honeycomb			 Extruded Polystyrene		
<b>Face Materials</b>								
 Eucalyptus Hardboard  Fiberboard  3-Ply Italian Poplar Plywood			 Eucalyptus Hardboard  Fiberboard  3-Ply Italian Poplar Plywood			 Eucalyptus Hardboard  Fiberboard  3-Ply Italian Poplar Plywood		
<b>Weight/Square Foot</b>								
0.6 - 1.3 lbs (Depending on Face Materials)			0.7 - 1.4 lbs (Depending on Face Materials)			0.6 - 1.3lbs (Depending on Face Materials)		
<b>Thickness Range</b>								
1/2" - 3"			1/2" - 1 1/2"			1/2" - 3"		
<b>Panel Sizes</b>								
48" x 96"   48" x 120" 48" x 144"   60" x 144"			48" x 96"   48" x 120" 48" x 144"   60" x 144"			48" x 96"   48" x 120" 48" x 144"   60" x 144"		
<b>Ease of Edge Banding</b>								
★ ★ ★ ☆ ☆			★ ★ ★ ★ ★			★ ★ ★ ☆ ☆		
<b>Paintable Edges</b>								
★ ★ ☆ ☆ ☆			☆ ☆ ☆ ☆ ☆			★ ★ ★ ★ ★		
<b>R Value</b>								
R4.4 for 1"			Unspecified			R5 for 1"		
<b>Fire Rating</b>								
 ASTM E 84: Class A (Core Only)			ASTM E 84: Class C			 ASTM E 84: Class A (Core Only)		
<b>Sustainability</b>								
-						-		
<b>Key Core Differentiators</b>								
<ul style="list-style-type: none"> <li>• 2.0lb density</li> <li>• Manufactured in expanded process leading to edges with visible polystyrene beads</li> </ul>			<ul style="list-style-type: none"> <li>• 3/8" hex cell structure</li> <li>• Non-foam product</li> <li>• 100% recycleable and biodegradeable</li> <li>• Best for automated edgebanding</li> </ul>			<ul style="list-style-type: none"> <li>• 2.0lb density</li> <li>• Manufactured in extruded process leading to smooth cut edges that can even be painted</li> <li>• Dow® Product</li> </ul>		