


WORKLITE® PANELS

EPS Foamkore®

XPS Foamkore®

			
Core Material			
 Expanded Polystyrene		 Extruded Polystyrene	
Face Materials			
 Eucalyptus Hardboard  Fiberboard  3-Ply Italian Poplar Plywood		 Eucalyptus Hardboard  Fiberboard  3-Ply Italian Poplar Plywood	
Weight/Square Foot			
0.6 - 1.3 lbs (Depending on Face Materials)		0.6 - 1.3lbs (Depending on Face Materials)	
Thickness Range			
1/2" - 3/4"		1/2" - 3"	
Panel Sizes			
48" x 96" 48" x 120" 48" x 144" 60" x 144"		48" x 96" 48" x 120" 48" x 144" 60" x 144"	
Ease of Edge Banding			
★ ★ ★ ☆ ☆		★ ★ ★ ☆ ☆	
Paintable Edges			
★ ★ ☆ ☆ ☆		★ ★ ★ ★ ★	
R Value			
R4.4 for 1"		R5 for 1"	
Fire Rating			
 ASTM E 84: Class A (Core Only)		 ASTM E 84: Class A (Core Only)	
Sustainability			
-		-	
Key Core Differentiators			
<ul style="list-style-type: none"> • 2.0lb density • Manufactured in expanded process leading to edges with visible polystyrene beads 		<ul style="list-style-type: none"> • 2.0lb density • Manufactured in extruded process leading to smooth cut edges that can even be painted 	